

SHUR-GRIP

SKID RESISTANCE ADDITIVE FOR SEALERS

DESCRIPTION

Increte Systems SHUR-GRIP is a colorless, finely graded, polypropylene non-slip additive for sealers and coatings, leaving a unique textured durable surface. SHUR-GRIP particles are spherical to extend the wear resistance within the coating and will stay suspended in solution without continuous stirring.

FEATURES

- Helps to prevent slips and falls
- Colorless
- Neutral buoyancy—doesn't settle or float quickly
- Works in solvent and water based systems

TECHNICAL INFORMATION

Composition: Polypropylene powder.
Particle Size: 50 Mesh

Can be used to create a static coefficient of friction of 0.8 or greater.
Results may vary depending on coating, substrate and application techniques.

PACKAGING

1 pound, 3 pound, or 15 pound units

SHELF LIFE

4+ years in original, unopened containers

COVERAGE

SHUR-GRIP is added at 8 fluid ounces (1 scoop) per gallon or one pound per five gallons of sealer.



Decorative Concrete
Technology

INCRETE SYSTEMS

1611 Gunn Hwy. Odessa, FL 33556

Phone: 813-886-8811 - Toll-Free: 800-752-4626 - Fax: 813-920-1516

www.increte.com

A Division of The Euclid Chemical Company An **RPM** Company

SHUR-GRIP

SKID RESISTANCE ADDITIVE FOR SEALERS

DIRECTIONS FOR USE

APPLICATION PROCESS

SHUR-GRIP can be used in most sealers and coatings where increased slip resistance is desired. SHUR-GRIP can be used indoors or outdoors, especially over decorative concrete surfaces where other non-skid materials can not be used because of their color.

Procedure – Mix sealer or coating to proper consistency. Slowly add prescribed amount of SHUR-GRIP and remix until properly dispersed. Apply sealer or coating as directed without over rolling. SHUR-GRIP is fine enough that it can also be used in most spray applications.

PRECAUTIONS/LIMITATIONS

When finely divided and suspended in air, this product could be flammable. Keep away from heat, sparks, and open flame. Use with adequate ventilation.

KEEP AWAY FROM CHILDREN.

WARRANTY All recommendations, statements and technical data contained herein based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his use of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person having any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations or statements other than those contained in written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

IMPORTANT NOTICE: THESE PRODUCTS ARE SOLD SUBJECT ONLY TO THE EXPRESSED WARRANTIES CONTAINED HEREIN. ADDITIONAL WARRANTIES, EXPRESSED OR IMPLIED, AND ANY WARRANTY OF MERCHANTABILITY IS HEREBY EXCLUDED. BUYER AGREES THAT SELLER ASSUMES NO LIABILITY FOR CONSEQUENTIAL DAMAGES OF ANY KIND, WHICH RESULT FROM THE USE OR MISUSE OF THE MERCHANDISE SOLD HEREUNDER. IN THE EVENT THAT THE BUYER PROVES THAT ANY GOODS RECEIVED DO NOT CONFORM TO THE SPECIFICATIONS AGREED TO BETWEEN THE PARTIES OR IF THE BUYER PROVES THAT SUCH GOODS WERE DEFECTIVELY MANUFACTURED, THE BUYER'S REMEDIES SHALL BE LIMITED TO EITHER THE RETURN OF THE GOODS AND REPAYMENT OF THE PURCHASE PRICE OR REPLACEMENT OF THE NON-CONFORMING GOODS AT THE OPTION OF THE SELLER. SUCH REMEDY BEING EXCLUSIVE OF ALL OTHERS AND THE SOLE REMEDY AVAILABLE TO THE BUYER, HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.